



SprayMax Silicone Remover 6620S is a mixture of slowly-evaporating organic solvents. Thanks to its anti-static effect it removes oil and grease residues from both metal and also plastic surfaces.

- · High-quality multi-purpose Silicone Remover.
- · Can also be used for plastic parts.
- · 400 ml spray can.

Multi-purpose degreasing agent to remove oil and grease residues on metal and plastic.



#### **Product preparation - application Preparatory Cleaner**



It is strongly recommended to use appropriate personal protection equipment during application to avoid respiratory, skin and eye irritation.





Old or original paintwork unsanded.

Old or original paintwork well sanded.

OEM Primer (e-coat), unsanded.

OEM Primer (e-coat), sanded.

Galvanised steel or soft aluminium sanded.

Glass fibre reinforced polyester substrates, free of release agents sanded.

Surfaces pretreated with 2K polyester products and then finely sanded.

Wipe dry with a clean cloth.

Change cloths often, never use dirty cloths.

Never let Standox Spray Max Silicone Remover 6620S evaporate from the surface. Treat only one small area at the time.



Spray distance: keep 15 - 20 cm distance.



Not applicable

VOC compliant

2004/42//IIB(a)(850) 770: The EU limit value for this product (product category: IIB(a)) in ready to use form is maximum 850 g/l of VOC. The VOC content of this product in ready to use form is maximum 770 g/l

#### **Product preparation - application Plastic Preparatory**



It is strongly recommended to use appropriate personal protection equipment during application to avoid respiratory, skin and eye irritation.





Repairs to exterior common plastic car parts, sanded and cleaned.

New exterior common plastic car parts, tempering 60 min. 60-65°C / first cleaning use a pad ultrafine soaked in Standox Spray Max Silicone Remover 6620S / final cleaning use a cloth moistened with Standox Spray Max Silicone Remover 6620S.

Wipe surface to loosen and lift contaminants. Immediately, thoroughly wipe off with a clean cloth. Change cloths often, never use dirty cloths.



Spray distance: keep 15 - 20 cm distance.



Not applicable

VOC compliant

2004/42//IIB(a)(850) 770: The EU limit value for this product (product category: IIB(a)) in ready to use form is maximum 850 g/l of VOC. The VOC content of this product in ready to use form is maximum 770 g/l.

### **Product preparation - application Final Cleaner**



It is strongly recommended to use appropriate personal protection equipment during application to avoid respiratory, skin and eye irritation.





Old or original paintwork well sanded.

Glass fibre reinforced polyester substrates, free of release agents sanded.

Wipe dry with a clean cloth.

Change cloths often, never use dirty cloths.

Never let Standox Spray Max Silicone Remover 6620S evaporate from the surface. Treat only one small area at the time.



Spray distance: keep 15 - 20 cm distance.



Not applicable

VOC compliant

This product mix is not VOC compliant.

#### **Products**

Standox SprayMax Silicone Remover 6620S

Consult Safety Data Sheet prior to use. Observe the precautionary notices displayed on the container.

All other products referred to in the refinish build up are from our Standox product range. System properties will not be valid when the related material is used in combination with any other materials or additives which are not part of our Standox product range, unless explicitly indicated otherwise.

For professional use only! The information provided in this documentation has been carefully selected and arranged by us. It is based upon our best knowledge on the subject at the date of issuance. The Information is given for information purposes only. We are not liable for its correctness, accuracy and completeness. It is up to the user to check the information with regard to up-to-dateness and suitability for his intended purpose. The intellectual property in this Information, including patents, trademarks and copyrights, is protected. All rights reserved. The relevant Material Safety Data Sheet and Warnings displayed on the product label need to be observed. We may modify and/ or discontinue operation of all or portions of this Information at any time in our sole discretion, without notice and assume no responsibility to update the Information. All rules set forth in this clause shall apply accordingly for any future changes and amendments.