

Standox Silicone Remover Xylene free 6650



Solvent-based cleaning agent for preparing surfaces that are to be painted.

- Silicone remover for cleaning surfaces that are to be painted with solvent-based base products or topcoats.




The Art of Refinishing.

Standex Silicone Remover Xylene free 6650


Product preparation - application Preparatory Cleaner



It is strongly recommended to use appropriate personal protection equipment during application to avoid respiratory, skin and eye irritation.



Old or original paintwork unsanded.
OEM Primer (e-coat), unsanded.
Bare steel sanded.
Galvanised steel or soft aluminium sanded.
Old or original paintwork well sanded.
OEM Primer (e-coat), sanded.
Glass fibre reinforced polyester substrates, free of release agents sanded.



Ready to use



Not applicable

VOC compliant


2004/42/IIB(a)(850) 770: The EU limit value for this product (product category: IIB(a)) in ready to use form is maximum 850 g/l of VOC. The VOC content of this product in ready to use form is maximum 770 g/l.

Standex Silicone Remover Xylene free 6650

Product preparation - application Final Cleaner



It is strongly recommended to use appropriate personal protection equipment during application to avoid respiratory, skin and eye irritation.



Old or original paintwork well sanded.

Primer, Primer-surfacer or Filler, sanded.

OEM Primer (e-coat), sanded.

Galvanised steel or soft aluminium sanded.

Surfaces pretreated with 2K polyester products and then finely sanded.

Glass fibre reinforced polyester substrates, free of release agents sanded.


Degrease the sanded surface with Standox Silicone Remover Xylene free 6650 just before application of Undercoats or Topcoats.

Wipe dry with a clean cloth.

Change cloths often, never use dirty cloths.

Never let Standox Silicone Remover Xylene free 6650 evaporate from the surface. Treat only one small area at the time.

Bare steel sanded.



Ready to use



Not applicable

VOC compliant

2004/42/IIIB(a)(850) 770: The EU limit value for this product (product category: IIIB(a)) in ready to use form is maximum 850 g/l of VOC. The VOC content of this product in ready to use form is maximum 770 g/l.

Standex Silicone Remover Xylene free 6650

Products

Standex Silicone Remover Xylene free 6650

Consult Safety Data Sheet prior to use. Observe the precautionary notices displayed on the container.

All other products referred to in the refinish build up are from our Standox product range. System properties will not be valid when the related material is used in combination with any other materials or additives which are not part of our Standox product range, unless explicitly indicated otherwise.

For professional use only! The information provided in this documentation has been carefully selected and arranged by us. It is based upon our best knowledge on the subject at the date of issuance. The Information is given for information purposes only. We are not liable for its correctness, accuracy and completeness. It is up to the user to check the information with regard to up-to-dateness and suitability for his intended purpose. The intellectual property in this Information, including patents, trademarks and copyrights, is protected. All rights reserved. The relevant Material Safety Data Sheet and Warnings displayed on the product label need to be observed. We may modify and/ or discontinue operation of all or portions of this Information at any time in our sole discretion, without notice and assume no responsibility to update the Information. All rules set forth in this clause shall apply accordingly for any future changes and amendments.

